



T7170 Product Specifications

FEATURE	T7170
DRIVE	
Tractor PTO RPM Rated Speed	540
Gearbox	Heavy-Duty Comer Gearbox
Drive Chain	Double 120 Roller Chain
Rotor Width	7'
Number of Rotor Teeth	126
Rows of Rotor Teeth	3 - Revolutionary
Rotor Bearings (Both Sides)	Footed Spherical 3-7/16"
Jackshaft Size and Bearings (Both)	Footed Spherical 3-7/16"
CONVEYOR	
Single Wide Chain Conveyor with CA550 Chain	Standard
Hydraulic Conveyor Winch	Standard
HYDRAULICS	
Self-Contained Hydraulics	Standard
External Reservoir	Standard
CABLE AND BACKSTOP	
Cable Length (approximate)	300' Standard
Cable Brakes	Dual Disc Industrial Brake
Brake Hand Pump	Standard
Hydraulic Cable Rewind	Standard
Steel Backstop with Multiple Pick Points	Standard
Maximum Ag-Bag Length	300'
TUNNELS AND EXTENSIONS	
9' Tunnel Top	Yes - Interchangeable
10' Tunnel Top	Yes - Interchangeable
9' x 34" Tunnel Extension	Standard with 9' Tunnel Top
10' x 34" Tunnel Extension	Standard with 10' Tunnel Top
9' x 34" Middle Extension	Optional
10' x 34" Middle Extension	Optional
BAG BOOM AND CRADLE	
Bag Boom with Brake Style Winch	Standard
Bag Cradle with Tunnel Lift Capability	Standard
INOCULANT APPLICATION	
Dry or Liquid	Optional
SPECIFICATIONS	
Overall Width (Transport)	8' 6"
Overall Width (Ag-Bagging)	21'
Overall Length (Transport)	20' 2"
Overall Length (Ag-Bagging) (approx)	12' w/o Ext, 14' w/ Std Ext, 17' w/ Mid Ext
Overall Transport Height (for farm)	12' 6"
Overall Transport Height (from factory)	10' 6"
Overall Weight (w/10' Tunnel and Mid Ext, approx)	12,500 lbs
Tongue Weight (w/10' Tunnel and Mid Ext, approx)	1,600 lbs (Transport)
Horsepower Minimum	100 hp
Horsepower Maximum	170 hp