



# T7060 Product Specifications

FEATURE	T7060
<b>DRIVE</b>	
Tractor PTO RPM Rated Speed	540
Gearbox	Heavy-Duty Comer Gearbox
Drive Chain	Double 120 Roller Chain
Rotor Width	6'
Number of Rotor Teeth	108
Rows of Rotor Teeth	3 - Revolutionary
Rotor Bearings (Both Sides)	Footed Spherical 3-7/16"
Jackshaft Size and Bearings (Both)	Footed Spherical 3-7/16"
<b>CONVEYOR</b>	
Single Wide Chain Conveyor with CA550 Chain	Standard
Hydraulic Conveyor Winch	Standard
<b>HYDRAULICS</b>	
Self-Contained Hydraulics	Standard
External Reservoir	Standard
<b>CABLE AND BACKSTOP</b>	
Cable Length (approximate)	300' Standard
Cable Brakes	Dual Disc Industrial Brake
Brake Hand Pump	Standard
Hydraulic Cable Rewind	Standard
Steel Backstop with Multiple Pick Points	Standard
Maximum Ag-Bag Length	300'
<b>TUNNELS AND EXTENSIONS</b>	
6' Tunnel	Yes - Interchangeable
8' Tunnel Top	Yes - Interchangeable
9' Tunnel Top	Yes - Interchangeable
8' x 34" Tunnel Extension	Standard with 8' Tunnel Top
9' x 34" Tunnel Extension	Standard with 9' Tunnel Top
8' x 34" Middle Extension	Optional
9' x 34" Middle Extension	Optional
<b>BAG BOOM AND CRADLE</b>	
Bag Boom with Brake Style Winch	Optional for 6' Tunnel - Req'd for other tunnels
Bag Cradle with Tunnel Lift Capability	Optional for 6' Tunnel - Req'd for other tunnels
<b>INOCULANT APPLICATION</b>	
Dry or Liquid	Optional
<b>SPECIFICATIONS</b>	
Overall Width (Transport)	8' 6"
Overall Width (Ag-Bagging)	20'
Overall Length (Transport)	19' 2"
Overall Length (Ag-Bagging) (approx)	12' w/o Ext, 14' w/ Std Ext, 17' w/ Mid Ext
Overall Transport Height (for farm)	12' 6"
Overall Transport Height (from factory)	10' 6"
Overall Weight (w/10' Tunnel and Mid Ext, approx)	10,500 lbs
Tongue Weight (w/10' Tunnel and Mid Ext, approx)	1,500 lbs (Transport)
Horsepower Minimum	100 hp
Horsepower Maximum	170 hp