



T8088 Product Specifications

FEATURE	T8088
DRIVE	
Driveline	1000-RPM Planetary Driveline
Drive Chain	Double 120 Roller Chain
Rotor Width	104-inches
Number of Rotor Teeth	156
Rows of Rotor Teeth	3 - Revolutionary
Rotor Bearings (Both Sides)	Footed Spherical 3-7/16"
Jackshaft Size and Bearings (Both)	Footed Spherical 3-7/16"
CONVEYOR	
Single Wide Chain Conveyor with CA550 Chain	Standard
Hydraulic Conveyor Lift	Standard
HYDRAULICS	
Self-Contained Hydraulics	Standard
External Reservoir	Standard
Hydraulic Jack System	Standard
COMPACTION SYSTEM	
Anchor Positioning System	Standard - Two adjustable steel anchors
Anchor Travel Distance	0' to 6' - Infinite Adjustment
Wheel Brakes	Standard - Hyd Disc Brake
Brake Hand Pump	Standard
Maximum Ag-Bag Length	500'
TUNNELS AND EXTENSIONS	
10' Tunnel Top	Yes - Interchangeable
12' Tunnel Top	Yes - Interchangeable
10' x 40" Tunnel Extension	Standard with 10' Tunnel Top
12' x 40" Tunnel Extension	Standard with 12' Tunnel Top
Sweeping Tunnel Cleanout	Standard
BAG BOOM AND CRADLE	
Bag Boom with Brake Style Winch	Standard
Bag Cradle with Tunnel Lift Capability	Standard
INOCULANT APPLICATION	
Dry or Liquid	Optional
SPECIFICATIONS	
Overall Width (Transport)	8' 6"
Overall Width (Ag-Bagging)	18'
Overall Length (Transport)	22'
Overall Length (Ag-Bagging) (approx)	13' w/o Ext, 16' 4" w/ Std Ext
Overall Transport Height (for farm)	12' 6"
Overall Transport Height (from factory)	10' 6"
Overall Weight (w/12' Tunnel, approx)	13,500 lbs
Tongue Weight (w/12' Tunnel, approx)	1,800 lbs (Transport)
Horsepower Minimum	150 hp
Horsepower Maximum	220 hp