



## T7270, T7170 & T7060 Product Specifications

FEATURE	T7060	T7170 & T7270
<b>DRIVE</b>		
Tractor PTO RPM Rated Speed	540	T7170 - 540, T7270 - 1000
Gearbox	Heavy-Duty Comer Gearbox	Heavy-Duty Comer Gearbox
Drive Chain	Double 120 Roller Chain	Double 120 Roller Chain
Rotor Width	6'	7'
Number of Rotor Teeth	108	126
Rows of Rotor Teeth	3 - Revolutionary	3 - Revolutionary
Rotor Bearings (Both Sides)	Footed Spherical 3-7/16"	Footed Spherical 3-7/16"
Jackshaft Size and Bearings (Both)	Footed Spherical 3-7/16"	Footed Spherical 3-7/16"
<b>CONVEYOR</b>		
Single Wide Chain Conveyor with CA550 Chain	Standard	Standard
Hydraulic Conveyor Lift	Standard	Standard
<b>HYDRAULICS</b>		
Self-Contained Hydraulics	Standard	Standard
External Reservoir	Standard	Standard
Hydraulic Jack System	NA	Standard
<b>CABLE AND BACKSTOP</b>		
Cable Length (approximate)	300' Standard	300' Standard
Cable Brakes	Dual Disc Industrial Brake	Dual Disc Industrial Brake
Brake Hand Pump	Standard	Standard
Hydraulic Cable Rewind	Standard	Standard
Steel Backstop with Multiple Pick Points	Standard	Standard
Maximum Ag-Bag Length	300'	300'
<b>TUNNELS AND EXTENSIONS</b>		
6' Tunnel Top	Yes - Interchangeable	NA
8' Tunnel Top	Yes - Interchangeable	NA
9' Tunnel Top	Yes - Interchangeable	Yes- Interchangeable
10' Tunnel Top	NA	Yes- Interchangeable
6' x 34" Tunnel Extension	Standard with 6' Tunnel Top	NA
8' x 34" Tunnel Extension	Standard with 8' Tunnel Top	NA
9' x 34" Tunnel Extension	Standard with 9' Tunnel Top	Standard with 9' Tunnel Top
10' x 34" Tunnel Extension	NA	Standard with 10' Tunnel Top
8' x 34" Middle Extension	Optional	NA
9' x 34" Middle Extension	Optional	Optional
10' x 34" Middle Extension	NA	Optional
Sweeping Tunnel Cleanout	NA	Standard
<b>BAG BOOM AND CRADLE</b>		
Bag Boom with Brake Style Winch	Optional for 6' Tunnel - Standard for 8'/9'/10' tunnels	
Bag Cradle with Tunnel Lift Capability	Optional for 6' Tunnel - Standard for 8'/9'/10' tunnels	



## T7270, T7170 & T7060 Product Specifications

INOCULANT APPLICATION		
Dry or Liquid	Optional	Optional
SPECIFICATIONS		
Overall Width (Transport)	8' 6"	8' 6"
Overall Width (Ag-Bagging)	20'	21'
Overall Length (Transport)	19' 2"	20' 2"
Overall Length (Ag-Bagging) (approx)	12' w/o Ext, 14' w/ Std Ext, 17' w/ Mid Ext	12' w/o Ext, 14' w/ Std Ext, 17' w/ Mid Ext
Overall Transport Height (for farm)	12' 6"	12' 6"
Overall Transport Height (from factory)	10' 6"	10' 6"
Overall Weight (w/9' Tunnel and Mid Ext, approx)	11,000 lbs	12,500 lbs
Tongue Weight (w/9' Tunnel and Mid Ext, approx)	1,600 lbs (Transport)	1,600 lbs (Transport)
Horsepower Minimum	100 hp	100 hp
Horsepower Maximum	170 hp	170 hp