

# T9096 AG-BAGGER



## Tractor-Powered Table Ag-Bagger Rated to 350 hp

Your operation is growing. You need the highest quality forage and best efficiency in everything you do. The T9096 Tractor-Powered Table Bagger is the next step in the transformation of Ag-Bag. The T9096 enables producers to use their own power units while gaining the efficiency of a rear unloading table Ag-Bagger. The T9096 provides higher capacity, heavy-duty components and easy-to-use controls all while maximizing efficiency to meet the growing demand of your forage operation.



## T9096 Ag-Bagger Features:

- 350 hp Power Rating
- 9 ft. 6 in. Rotor
- 10- and 12-foot Tunnel Options
- 12-foot Wide Feed Table
- Direct Drive Feed Table (SCV)
- Operation from Tractor Cab
- Gearbox and Planetary Cooling
- Hydraulic Jacks
- Reversible Top Beater
- Integrated Hydraulics
- Hydraulic Bag Pan, Boom and Winch
- Anchor Position Control
- No Backstop
- Heavy Duty Wheel Braking
- Pintle Hitch Transport
- Sweeping Tunnel Cleanout
- Extra Ag-Bag Storage
- Storage Toolbox
- Narrow Transport
- Optional Tractor 3-Pt Transport
- Adjustable Hitch for all Tractors



**Better Storage  
Better Forage**

## T9096 Specifications:

FEATURE	T9096
<b>DRIVE</b>	
Driveline	1000-RPM Planetary Driveline
Gearbox and Planetary Cooling System	Standard
Direct Drive w/ Chain Coupler	Standard
Rotor Width	9' 6"
Number of Rotor Teeth	110
Rotor Style	Ag-Bag Legacy Rotor Pattern
Rotor Bearing (Drive)	Footed Spherical 3-15/16"
Rotor Bearing (Idler)	Footed Spherical 3-7/16"
Reversible Top Beater Drive	Standard
<b>FEED TABLE</b>	
12' Wide Opening Width	Standard
Single Wide Endless Belt	Standard
Hydraulic Lift	Standard
Direct Drive (from tractor SCV)	Standard
Heavy Duty Sealing System	Standard
<b>HYDRAULICS</b>	
Self-Contained Hydraulics With Cooler	Standard
External Reservoir	Standard
Hydraulic Jack System	Standard
<b>COMPACTION SYSTEM</b>	
Anchor Positioning System	Standard – Two adjustable steel anchors
Anchor Travel Distance	0' to 6' – Infinite Adjustment
Wheel Brakes	Standard – Hyd. Disc Brake
Brake Hand Pumps	2 – Standard
Maximum Ag-Bag Length	500'
<b>TUNNELS AND EXTENSIONS</b>	
10' Tunnel	Yes – Interchangeable
12' Tunnel	Yes – Interchangeable
10' x 40" Tunnel Extension	Standard with 10' Tunnel Top
12' x 40" Tunnel Extension	Standard with 12' Tunnel Top
Sweeping Tunnel Cleanout	Standard
<b>BAG BOOM, CRADLE, AND PAN</b>	
Hydraulic Bag Boom with Winch	Standard
Bag Cradle with Tunnel Lift Capability	Standard
Hydraulic Bag Pan with Fold-Down Gate	Standard
<b>INOCULANT APPLICATION</b>	
Dry or Liquid	Optional
<b>SPECIFICATIONS</b>	
Overall Width (Transport)	8' 6"
Overall Width (Ag-Bagging)	24' + Tractor
Overall Length (Transport)	30' (22' 6" without hitch)
Overall Length (Ag-Bagging) (approx)	21'
Overall Transport Height (for farm)	13' 6" (on pintle hitch at truck)
Overall Transport Height (from factory)	12' 6" (on ground)
Overall Weight (w/12' Tunnel, approx)	28,780 lbs.
Tongue Weight (w/12' Tunnel, approx)	10,000 lbs. (Transport)
Horsepower Minimum	225 hp
Horsepower Maximum	350 hp

208 River Knoll Drive  
Mayville, WI 53050  
1-800-334-7432  
[www.ag-bag.com](http://www.ag-bag.com)

