



# T9096 Tractor-Powered Table Ag-Bagger

## Product Specifications

<b>T9096 SPECIFICATIONS</b>	
<b>FEATURE</b>	
<b>DRIVE</b>	
Driveline	1000-RPM Planetary Driveline
Gearbox and Planetary Cooling System	Standard
Direct Drive w/ Chain Coupler	Standard
Rotor Width	9' 6"
Number of Rotor Teeth	110
Rotor Style	Ag-Bag Legacy Rotor Pattern
Rotor Bearing (Drive)	Footed Spherical 3-15/16"
Rotor Bearing (Idler)	Footed Spherical 3-7/16"
Reversible Top Beater Drive	Standard
<b>FEED TABLE</b>	
12' Wide Opening Width	Standard
Single Wide Endless Belt	Standard
Hydraulic Lift	Standard
Direct Drive (from tractor SCV)	Standard
Heavy Duty Sealing System	Standard
<b>HYDRAULICS</b>	
Self-Contained Hydraulics With Cooler	Standard
External Reservoir	Standard
Hydraulic Jack System	Standard
<b>COMPACTION SYSTEM</b>	
Anchor Positioning System	Standard - Two adjustable steel anchors
Anchor Travel Distance	0' to 6' - Infinite Adjustment
Wheel Brakes	Standard - Hyd Disc Brake
Brake Hand Pumps	2, Standard
Maximum Ag-Bag Length	500'
<b>TUNNELS AND EXTENSIONS</b>	
10' Tunnel	Yes - Interchangeable
12' Tunnel	Yes - Interchangeable
10' x 40" Tunnel Extension	Standard with 10' Tunnel Top
12' x 40" Tunnel Extension	Standard with 12' Tunnel Top
Sweeping Tunnel Cleanout	Standard
<b>BAG BOOM, CRADLE, AND PAN</b>	
Hydraulic Bag Boom with Winch	Standard
Bag Cradle with Tunnel Lift Capability	Standard
Hydraulic Bag Pan with Fold-Down Gate	Standard
<b>INOCULANT APPLICATION</b>	
Dry or Liquid	Optional



# T9096 Tractor-Powered Table Ag-Bagger

## Product Specifications

SPECIFICATIONS	
Overall Width (Transport)	8' 6"
Overall Width (Ag-Bagging)	24' + Tractor
Overall Length (Transport)	30' (22' 6" without hitch)
Overall Length (Ag-Bagging) (approx)	21'
Overall Transport Height (for farm)	13' 6" (on pintle hitch at truck)
Overall Transport Height (from factory)	12' 6" (on ground)
Overall Weight (w/12' Tunnel, approx)	28,780 lbs
Tongue Weight (w/12' Tunnel, approx)	10,000 lbs (Transport)
Horsepower Minimum	225 hp
Horsepower Maximum	350 hp